

4 SOCKET DISTRIBUTION UNIT: 2 - 1PH+N+PE / 2 - 3PH+N+PE

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX PLUGS & SOCKETS

ZONES 1, 2 (gas) & 21, 22 (dust)

ATEX-certified 4-outlet rack for fixed installation in hazardous areas. Hinged lid.

Equipped with 2 ATEX sockets 20A 220/250V 1PH+N+PE, 2 ATEX sockets 32A 380/440V 3PH+N+PE and their respective plugs.



EU-Type Examination Certificate

The cable gland is supplied separately

ITEM REFERENCES

Designation:	Rated current:	Rated voltage:	Poles:	Item No.:
4-outlet rack (2 - 1PH+N+PE 20A / 2 - 3PH+N+PE 32A)	20A 32A	220/250V 380/440V	1PH+N+PE 3PH+N+PE	6F0111

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex ed IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Material:	Polyester black
Dimensions:	400x250x120 mm
Operating conditions:	Indoor / Outdoor
Terminals:	9x10 mm ² and 3x10 mm ² PE
Outlets:	2 sockets 20A 1PH+N+PE 2 sockets 32A 3PH+N+PE
Ingress protection:	IP65
Operating temperature:	-20°C to +40°C
Cable entries:	1 M25x1,5

