

4 SOCKET DISTRIBUTION UNIT: 2 - 1PH+N+PE / 1 - 3PH+PE / 1 - 3PH+N+PE

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX PLUGS & SOCKETS

ZONES 1, 2 (gas) & 21, 22 (dust)

ATEX-certified 4-outlet rack for fixed installation in hazardous areas. Hinged lid.

Equipped with 2 ATEX 20A 220/250V 1PH+N+ PE sockets, 1 ATEX 32A 380/440V 3PH+ PE socket and 1 ATEX 32A 380/440V 3PH+N+PE socket with their respective plugs.



The cable gland is supplied separately

ITEM REFERENCES

Designation:	Rated current:	Rated voltage:	Poles:	Item No.:
4-outlet rack (2 - 1PH+N+PE 20A / 1 - 3PH+PE 32A / 1 - 3PH+N+PE 32A)	20A 32A	220/250V 380/440V	1P+N+T 3P+T 3P+N+T	6F0114

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex ed IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Material:	Polyester black
Dimensions:	400x250x120 mm
Operating conditions:	Indoor / Outdoor
Terminals:	12x10 mm ² y 3x10 mm ² PE
Outlets:	2 sockets 1P+N+T 20A 1 socket 3P+T 32A 1 socket 3P+N+T 32A
Ingress protection:	IP65
Operating temperature:	-20°C to +40°C
Cable entries:	1 M32x1,5

