

2 SELECTOR SWITCH CONTROL STATION

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



Control stations equipped with 2 0-I selector switches for hazardous areas, made of glass-fibre reinforced polyester for use in explosive atmospheres.

Fitted with M20 brass or nickel-plated brass cable glands for armoured cable or polyamide cable glands for installation with non-armoured cable.



EU-Type Examination Certificate

ITEM REFERENCES

Designation:	Item No.:
2 Selector Switch Control Station - Brass Cable Gland	3J1101
2 Selector Switch Control Station - Nickel Plated Brass Cable Gland	3J1102
2 Selector Switch Control Station - Plastic Cable Gland	3J1103

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex db eb IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Cable entries:	1xM20x1,5

INTERNAL CONTACT MODULE



Marking:	Ex II 2G Ex de IIC Gb Ex I M2 Ex de I Mb		
Certificate:	EU-Type Examination Certificate		
Operating temperature:	-55°C to +60°C		
Ingress protection:	IP20		
Nominal isolation voltage:	690 V		
Voltage range:			
400 V	400 V	110 V	24 V
Utilization categories:			
AC-12	AC-15	DC-13	DC-13
Current range:			
16 A	10 A	0.5 A	1 A

