

AMMETER-START-EMERGENCY STOP CONTROL STATION

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com


ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



ATEX certified Control Panel equipped with an Ammeter, a Start pushbutton and an Emergency Mushroom.

With brass or nickel-plated brass M25 cable gland for installation with armoured cable or polyamide M25 cable gland for unarmoured cable.



ITEM REFERENCES

Designation:	Item No.:
AMMETER - START 2NO - EMERGENCY STOP 2NC Control Station - Brass Cable Gland	3J0501
AMMETER - START 2NO - EMERGENCY STOP 2NC Control Station - Nickel-plated Brass Cable Gland	3J0502
AMMETER - START 2NO - EMERGENCY STOP 2NC Control Station - Plastic Cable Gland	3J0503

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex db eb IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Dimensions:	220x122x90 mm
Material:	Glass fibre reinforced polyester (GRP)
Ingress protection:	IP65
Operating temperature:	-20°C to +40°C
Ammeter:	Range 0-300A / Full scale 450A / Current transformet 300/1A
Terminals:	8 x 2,5 mm ² (1-8) + 1 x PE
Cable entries:	1xM25x1,5 Armoured Cable (14-20,5 mm) Non-Armoured Cable (10 - 17 mm)

earth lug for cable gland M25x1,5

