

SWITCHES SERIE EFS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX SWITCHES

ZONES 1, 2 (gas) & 21, 22 (dust)



Explosion-proof breakers, selector switches, connecting switches series EFS.











Rotating type, with its knob on the front.

Suitable for currents up to 16A and voltages up to 690 VAC / 660 VDC.



EU-Type Examination Certificate

ITEM REFERENCES


	Designation:	Contacts:	Item No.:		Designation:	Contacts:	Item No.:
	EFS 116 N	1 pole, (0/1) switches	3G0101		EFS 316 N	3 pole, (0/1) switches / 400V / AC3 / 5,5 kW max.	3G0103
	EFS 216 N	2 pole, (0/1) switches	3G0102		EFS 416 N	4 pole, (0/1) switches / 400V / AC3 / 5,5 kW max.	3G0104
	EFS 116/CN	1 pole mains transfer switches (1/0/2)	3G0105		EFS 316/CN	3 pole mains transfer switches (1/0/2)	3G0107
	EFS 216/CN	2 pole mains transfer switches (1/0/2)	3G0106				
	EFS 116/DN	1 pole change-over switches (1/2)	3G0108		EFS 316/DN	3 pole change-over switches (1/2)	3G0110
	EFS 216/DN	2 pole change-over switches (1/2) K3022 AC1 2A AC3/3PH 220V - 5,5kW 300V - 11kW 600V - 15kW	3G0109				

SWITCHES SERIE EFS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

TECHNICAL SPECIFICATIONS

Marking:	 II 2G Ex d IIB T6-T5 Gb (IIC on request) II 2D Ex tb IIIC T85°C-T100°C Db
Certificate:	EU-Type Examination Certificate
Housing:	Aluminium (RAL 7000)
Rated voltage:	Max. 690 VAC / 660 VDC.
Rated current:	Max. 16A
Operating temperature:	-20°C to +40°C
Ingress protection:	IP66/67
Weight:	700 g
Cable entries:	2x3/4" NPT (cable glands not included)

