ATEX PORTABLE LAMPS

ZONES 1, 2 (gas) & 21, 22 (dust)



Explosion-proof certified portable lamp for use in hazardous areas.

Suitable for incandescent, halogen, energysaving and LED lamps.

Housing in aluminium light alloy.

Cage, hook and handle covered with Nylon.



ITEM REFERENCES									
Model:	Lamp:	Lamp holder:		Temp. class:		T Cables	Waisht.	Itam Na i	
				Gas	Dust	T. Cable:	Weight:	Item No.:	
EVP 50	Energy-saving up to 15W		E27	T4	T135°C	NC	- 1,8 Kg	1D0301	
	LED up to 9W			Т6	T85°C	NC			
	Incandescent up to 100W			Т3	T200°C	160°C			
	Halogen up to 100W			Т3	T200°C	160°C			

TECHNICAL SPECIFICATIONS						
Marking:	II 2G Ex d IIC T6-T3 Gb					
Certificate:	EU-Type Examination Certificate					
Lamp:	Halogen, Incandescent, Energy-saving or LED					
Rated voltage:	AC max.: 440 V AC DC max.: 48 V DC					
Ingress protection:	IP65					
Operating temperature:	-20°C to +40°C					
Cable entries:	1/2" NPT (cable gland not included)					

ACCESSORIES								
Designation:	Cable length:	Item No.:						
	5 m	1D0203						
	10 m	1D0204						
Cable 1107DN F 450/750V 2C1 F	15 m	1D0205						
Cable H07RN-F 450/750V 3G1,5	20 m	1D0206						
	25 m	1D0207						
	30 m	1D0208						

