

EMERGENCY STOP WITH PROTECTION HOOD - ARMoured CABLE

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS


ZONES 1, 2 (gas) & 21, 22 (dust)



Ex e Emergency Stop mushroom button with protection hood made of glass fibre reinforced polyester for application in hazardous areas.

Equipped with M20 brass or nickel-plated brass cable glands for installation with armoured cable.

3,2x6mm metal protection in stainless steel SS316.



ITEM REFERENCES

Designation:	Item No.:	
	Emergency Mushroom Button w/ Protection Hood 1NO+1NC - M20 Brass Cable Gland	3J0107
	Emergency Mushroom Button w/ Protection Hood 2NC - M20 Brass Cable Gland	3J0108
	Emergency Mushroom Button w/ Protection Hood 2NO - M20 Brass Cable Gland	3J0109
	Emergency Mushroom Button w/ Protection Hood 1NO+1NC - M20 Nickel-Plated Brass Cable Gland	3J0110
	Emergency Mushroom Button w/ Protection Hood 2NC - M20 Nickel-Plated Brass Cable Gland	3J0111
	Emergency Mushroom Button w/ Protection Hood 2NO - M20 Nickel-Plated Brass Cable Gland	3J0112

INTERNAL CONTACT MODULE

Marking:	Ex II 2G Ex de IIC Gb Ex I M2 Ex de I Mb		
Certificate:	EU-Type Examination Certificate		
Operating temperature:	-55°C to +60°C		
Ingress protection:	IP20		
Nominal isolation voltage:	690 V		
Voltage range:			
400 V	400 V	110 V	24 V
Utilization categories:			
AC-12	AC-15	DC-13	DC-13
Current range:			
16 A	10 A	0,5 A	1 A

TECHNICAL SPECIFICATIONS

Marking:	Ex II 2G Ex ed IIC T6 Gb Ex II 2D Ex tb IIIC T80°C
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Cable entries:	1xM20x1,5 Brass or nickel-plated brass cable gland (14-20,5 mm)

