

EMERGENCY STOP WITH PROTECTION HOOD - NON ARMoured CABLE

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



Ex e Emergency Stop mushroom button with protection hood made of glass fibre reinforced polyester for application in hazardous areas.

Equipped with M20 brass or nickel-plated brass cable glands for installation with unarmoured cable.

3,2x6mm metal protection in stainless steel SS316.




EU-Type Examination Certificate

4






CONTROL & CONNECTION EQUIPMENT

ITEM REFERENCES



Designation:	Item No.:
 Emergency Mushroom Button w/ Protection Hood 1NO+1NC - M20 Plastic cable gland	3J0204
Emergency Mushroom Button w/ Protection Hood 2NC - M20 Plastic cable gland	3J0205
Emergency Mushroom Button w/ Protection Hood 2NO - M20 Plastic cable gland	3J0206

INTERNAL CONTACT MODULE



Marking:	 II 2G Ex de IIC Gb  I M2 Ex de I Mb
Certificate:	EU-Type Examination Certificate
Operating temperature:	-55°C to +60°C
Ingress protection:	IP20
Nominal isolation voltage:	690 V
Voltage range:	
400 V	400 V 110 V 24 V
Utilization categories:	
AC-12	AC-15 DC-13 DC-13
Current range:	
16 A	10 A 0,5 A 1 A

TECHNICAL SPECIFICATIONS

Marking:	 II 2G Ex ed IIC T6 Gb  II 2D Ex tb IIIC T80°C
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Cable entries:	1xM20x1,5 Plastic cable gland (7 - 13 mm)

