

# COMPACT S-S-E CONTROL STATION - ARMoured CABLE

Zones 1, 2, 21, 22

Full catalogue available on our website: [www.inpratex.com](http://www.inpratex.com)

## ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



Compact Start-Stop-Emergency Control Station made of glass fibre reinforced polyester for application in hazardous areas.

Equipped with M20 brass or nickel-plated brass cable glands for installation with armoured cable.



EU-Type Examination Certificate

### ITEM REFERENCES

Designation:	Item No.:
START-STOP (GREEN-RED) 1NO+1NC - EMERGENCY STOP 2NC Control Station - Brass Cable Gland	3J0304
START-STOP (GREEN-RED) 1NO+1NC - EMERGENCY STOP 2NC Control Station - Nickel Plated Brass Cable Gland	3J0305

### TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex ed IIC T6 Gb II 2D Ex tb IIIC T80°C
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Cable entries:	1xM20x1,5 Brass or nickel-plated brass cable gland (14-20,5 mm)

### INTERNAL CONTACT MODULE

Marking:	<div><div><div>Ex</div><div>Ex</div></div><div>II 2G Ex de IIC Gb I M2 Ex de I Mb</div></div>		
Certificate:	EU-Type Examination Certificate		
Operating temperature:	-55°C to +60°C		
Ingress protection:	IP20		
Nominal isolation voltage:	690 V		
Voltage range:			
400 V	400 V	110 V	24 V
Utilization categories:			
AC-12	AC-15	DC-13	DC-13
Current range:			
16 A	10 A	0,5 A	1 A

