

EX E, GRP EMERGENCY STOP - NON ARMoured CABLE

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com


ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)




Ex e Emergency Stop mushroom button made of glass fibre reinforced polyester for application in hazardous areas.



Equipped with M20 polyamide cable glands for installation with unarmoured cable.







ITEM REFERENCES

Designation:	Item No.:	
	Emergency Mushroom Button (e) 1NO+1NC - M20 Plastic cable gland	3J0201
	Emergency Mushroom Button (e) 2NC - M20 Plastic cable gland	3J0202
	Emergency Mushroom Button (e) 2NO - M20 Plastic cable gland	3J0203

TECHNICAL SPECIFICATIONS

Marking:	 II 2G Ex db eb IIC T6 Gb  II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Cable entries:	1xM20x1,5 Plastic cable gland (7 - 13 mm)

INTERNAL CONTACT MODULE

	
Marking:	 II 2G Ex de IIC Gb  I M2 Ex de I Mb
Certificate:	EU-Type Examination Certificate
Operating temperature:	-55°C to +60°C
Ingress protection:	IP20
Nominal isolation voltage:	690 V
Voltage range:	
400 V	400 V 110 V 24 V
Utilization categories:	
AC-12	AC-15 DC-13 DC-13
Current range:	
16 A	10 A 0,5 A 1 A