

GRP JUNCTION BOX 2 CABLE ENTRIES - 2 TERMINALS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

4



CONTROL & CONNECTION EQUIPMENT

ATEX JUNCTION BOXES

ZONES 1, 2 (gas) & 21, 22 (dust)



GRP (glass-reinforced polyester) junction box, suitable for use within ATEX rated Ex e Increased Safety areas.

Equipped with 2 cable entries and 2 2,5mm² + 1 PE terminals.



ITEM REFERENCES

Designation:	Cable glands:	Item No.:
A21-E1-01106+2T2,5+2M20	Without cable glands	5A1003
A21-E1-01106+2T2,5+1PM20+1PAM20	1 plastic cable gland (4-13 mm) + 1 brass cable gland (9-15,5 mm)	5A1004
A21-E1-01106+2T2,5+1PM20+1PANM20	1 plastic cable glands (4-13 mm) + 1 nickel plated brass cable gland (9-15,5 mm)	5A1005

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex eb IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Housing:	Glass Reinforced Polyester (GRP)
Dimensions:	110x75x55 mm
Operating temperature:	-20°C to +40°C
Rated voltage:	max. 550V
Rated current:	max. 21 A
Terminals:	2 x 2,5mm ² + 1 PE
Ingress protection:	IP65
Cable entries:	2xM20x1,5

