

GRP JUNCTION BOX 4 CABLE ENTRIES - 19 TERMINALS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX JUNCTION BOXES


ZONES 1, 2 (gas) & 21, 22 (dust)



ATEX junction boxes certified for installation in hazardous areas.

Manufactured in Glass Reinforced Polyester (GRP)

The box is configured with 4 unplugged M25x1.5 cable entries, and is equipped with 19 2.5mm² terminals, 3 grounding terminals and a brass grounding plate inside.



* Supplied without cable glands and plugs

ITEM REFERENCES

Designation:	Item No.:
A21-E1-02609+19T2,5+4M25	5A1001

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex eb IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Housing:	Glass Reinforced Polyester (GRP)
Dimensions:	260x160x90mm
Operating temperature:	-20°C to +40°C
Rated voltage:	max. 500V
Rated current:	max. 10 A
Terminals:	19 x 2,5mm ² + 3 PE
Ingress protection:	IP66
Cable entries:	4xM25x1,5 (Cable glands / plugs not included)

