

GRP JUNCTION BOX 7 CABLE ENTRIES - 10 TERMINALS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX JUNCTION BOXES

ZONES 1, 2 (gas) & 21, 22 (dust)



ATEX junction boxes certified for installation in hazardous areas.

Made from glass-fibre-reinforced polyester.

The box is configured with 2x M16x1.5, 1x M25x1.5 and 4x M20x1.5 cable entries, and is fitted with 10x 2.5 mm² terminals and 3 PE terminals inside.



EU-Type Examination Certificate



ITEM REFERENCES

Designation:	Item No.:
A21-E1-01609+10T2,5+2PM16+1PM25+4PM20	5A0827

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex eb IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Housing:	Glass Reinforced Polyester (GRP)
Dimensions:	160x160x90 mm
Rated voltage:	max. 500V
Rated current:	max. 13 A
Terminals:	10x 2,5mm ² + 3 PE
Ingress protection:	IP65
Cable entries:	2x M16 plastic cable glands (4-10 mm) 1x M25 plastic cable gland (10-17 mm) 4x M20 plastic cable glands (7-13 mm)

