

GRP JUNCTION BOX ZONE 2,22 - 4 ENTRIES NON ARMOURED CABLE

Zones 2, 22

Full catalogue available on our website: www.inpratex.com

4 CONTROL & CONNECTION EQUIPMENT

ATEX JUNCTION BOXES

ZONES 2 (gas) & 22 (dust)



ATEX junction box for hazardous areas (Zones 2,22).

Manufactured in fibreglass reinforced polyester.

It is equipped with 4 M20x1,5 entries for non armoured cable, 6 x 2,5mm² terminals and 4 x 2,5mm² PE terminals.



ITEM REFERENCES		
Designation:	Cable entries:	Item No.:
Junction Box EX 12212090 GRP P	4 x M20x1,5 plastic cable glands (7-13 mm)	5A0704
Junction Box EX 12212090 GRP T	4 x M20x1,5 plastic plugs	5A0705

TECHNICAL SPECIFICATIONS	
Marking:	II 3G Ex ec IIC T6 Gc II 3D Ex tc IIIC T80°C Dc
Certificate:	Declaration of conformity
Housing:	Glass Reinforced Polyester (GRP)
Dimensions:	122x120x90 mm
Operating temperature:	-20°C to +60°C -50°C to +60°C (Whenever permitted by the terminal used)
Terminals:	6 x 2,5mm ² with jumpers (1, 2/3, 4/5, 6) + 4 PE terminals 2,5mm ² (PE)
Ingress protection:	IP66 IK08
Cable entries:	4xM20x1,5 plastic cable glands for non armoured cable / plugs

