

START-STOP-EMERGENCY CONTROL STATION - NON ARMoured CABLE

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com


ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



Start-Stop-Emergency Control Station made of glass fibre reinforced polyester for application in hazardous areas.

Equipped with M25 polyamide cable glands for installation with unarmoured cable.



4



CONTROL & CONNECTION EQUIPMENT

ITEM REFERENCES

Designation:	Item No.:
START 2NO (GREEN) - STOP 2NC (RED) - EMERGENCY STOP 2NC Control Station - Plastic Cable Gland	3J0301
START 1NO+1NC (GREEN) - STOP 1NO+1NC (RED) - EMERGENCY STOP 2NC Control Station - Plastic Cable Gland	3J0302

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex db eb IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Cable entries:	1xM25x1,5 Plastic cable gland (10 - 17 mm)

INTERNAL CONTACT MODULE



Marking:	II 2G Ex de IIC Gb I M2 Ex de I Mb		
Certificate:	EU-Type Examination Certificate		
Operating temperature:	-55°C to +60°C		
Ingress protection:	IP20		
Nominal isolation voltage:	690 V		
Voltage range:			
400 V	400 V	110 V	24 V
Utilization categories:			
AC-12	AC-15	DC-13	DC-13
Current range:			
16 A	10 A	0,5 A	1 A