

JUNCTION BOX SERIE S

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX JUNCTION BOXES

ZONES 1, 2 (gas) & 21, 22 (dust)



Explosion-proof junction boxes ideal for routing and interconnecting the wires at the intersection of the conduits.

Supplied with rough surface or outside painted according to customer specifications.





EU-Type Examination Certificate

ITEM REFERENCES

Designation:	External dimensions (mm):					Internal dimensions (mm):			Mounting brackets (mm):		Weight:	Item No.:
	ØB	C	D	E	ØF	G	H	I	ØL	M		
SFX 16N MM 2-8	90	78	50	20	8	70	49	70	108	126	440 gr	5A0501
SFX 26N MM 2-8	90	78	50	20	8	70	49	70	108	126	440 gr	5A0502

TECHNICAL SPECIFICATIONS

Marking:	 II 2G Ex d IIC T6 Gb  II 2D Ex tb IIIC T85°C Db
Certificate:	EU-Type Examination Certificate
Housing:	Aluminum light alloy (Aluminox on request)
Operating temperature:	-20°C to +40°C
Terminals:	8 Terminals 2,5mm ²
Ingress protection:	IP66/67
Cable entries:	
SFX 16N MM 2-8	SFX 26N MM 2-8
1/2" NPT (ØA)	3/4" NPT (ØA)

