

# KE-LED-EX 5018 TUBE LUMINAIRE 360°

Zones 1, 2, 21, 22

Full catalogue available on our website: [www.inpratex.com](http://www.inpratex.com)

## LED LIGHT FITTINGS

ZONES 1, 2 (gas) & 21, 22 (dust)

The ATEX LED 360° tube luminaire is ideal for illuminating work in explosion-proof areas, such as cleaning work in tanks or silos.

The integrated diffuser foil ensures a glare-free and homogeneous light. Thanks to the optionally available accessories, the light is suitable for permanent or temporary installation.

- Circular LED light source of 360°
- 18x POWER LEDs | 6500K
- Polycarbonate protective tube
- Integrated diffuser film
- Electronic ballast with special protection
- Aluminium end fittings



EU-Type Examination Certificate



Silo suspension optional




## ITEM REFERENCES

Designation:	Power:	Luminous flux:	Colour T.:	Weight:	Item No.:
EX 5018 Tube Luminaire	10 W	1000 lm	6500K	1,5 kg	1D0602

## TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex eb mb o is IIC T4 Gb II 2D Ex tb op is IIIC T105° Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Rated voltage:	24V AC/DC
Current:	0,33 A
Power:	10 W
LED 360°:	18x POWER LED   Colour Rendering Index >70   Lifetime >50.000h
Protection class:	III
Ingress protection:	IP68-50m/5h
Protective tube:	Polycarbonat
Impact resistance:	IK10
Integrated diffuser film:	Yes
Energy efficiency class:	F
Cable:	10m H07RN-F 2x1 mm <sup>2</sup>



## DIMENSIONS

a	b	c	d	e	f	g	h	i
35	45	225	175	45	53	50	20	525

## ACCESSORIES

Designation:	Item No.:
Silo suspension	AS-EX 5018
Mounting bracket with lock	BFK D50 EX
Permanent magnet with mounting bracket	KM 50 EX-KL
Antistatic protective film to protect the polycarbonate tube	SFO-EX 5018

