

# COMPACT LIGHT FITTINGS SERIES ND8611-LED

Zones 2, 22

Full catalogue available on our website: [www.inpratex.com](http://www.inpratex.com)

## LED LIGHT FITTINGS

## ZONES 2 (gas) & 22 (dust)




Compact LED Light Fitting ideal for permanent lighting in confined spaces in areas at risk of explosion.

Robust fitting for rough environment.

Perfect by strained field conditions.

Homogeneous illumination by using frosted diffusers, comfortable perception of light.

Fast mounting through external mounting grounding clips.



Declaration of Conformity

### ITEM REFERENCES

Designation:	Power consumption:	Luminous flux:	Luminous efficacy:	Weight:	Item No.:
nD8611 L02 W	4W	150 lm	38 lm/W	0,8 kg	1A2305

### TECHNICAL SPECIFICATIONS

Marking:	II 3G Ex nR IIC T4 Gc II 3D Ex tc IIIC T80°C Dc
Certificate:	Declaration of Conformity
Operating conditions:	Indoor / Outdoor
Housing:	Diecast aluminium, natural finish
Cover:	Polycarbonate opalescent white
LED:	Linear module 6.500K, CRI > 80, L80 > 50.000h at max. ambient temperature
Operating temperature:	-20°C a +40°C
Operating frequency:	50/60 Hz
Rated voltage:	220-240 V AC
Ingress protection:	IP65
Connection terminals:	3 or 4 poles, clamping range max. 2,5mm <sup>2</sup> .
Cable entries:	1xM20x1,5 plastic cable gland

