ATEX PORTABLE LAMPS

ZONES 1, 2 (gas) & 21, 22 (dust)

Explosion-protected LED handlamp for ATEX zones 1/2 (gas) and 21/22 (dust). Handle made of rubber (EPDM) with suspension eye, strain relief and cable entry. Electrical kit made of die-cast aluminium with LED module and integrated ECG. Frosted PC cover, wire guard made of galvanised steel with hook for hanging up the handlamp.



ITEM REFERENCES					
Designation:	Power:	Luminous flux:	Luminous efficacy:	Weight:	Item No.:
e9310F	11 W	600 lm	55 lm/W	1,3 kg	1D0501

TECHNICAL SPECIFICATIONS				
Marking:	II 2G Ex eb mb op is IIC T4 Gb II 2D Ex op is tb IIIC T80°C Db			
Certificate:	EU-Type Examination Certificate			
Handle:	Made of rubber (EPDM), with suspension eye, cable relief			
Cover:	Polycarbonate, frosted			
Wire guard:	Round steel, cage hook for suspension purpose			
LED:	Approx. 6,500K, CRI typically 80			
Operating temperature:	-25°C to +40°C			
Rated voltage:	220/240V AC/DC			
Ingress protection:	IP66			
Cable entries:	M20 x 1,5mm ² with bend protection			





