

LPG-532-BJB-ZA-S337 CROSS LASER POINTER

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX INSTRUMENTATION

ZONES 1, 2 (gas) & 21, 22 (dust)



These explosion-proof laser pointers (laser class 2) are available with a green laser as standard (red laser available upon request). All devices are certified for use in hazardous areas, including Zones 1, 2, 21, and 22.

They are ideally suited for precise alignment and positioning tasks in potentially explosive environments.

No additional peripherals required.



EU-Type Examination Certificate

ITEM REFERENCES

| Designation: | Beam shape: | Dimensions: | Item No.: |
|---------------------|-------------------|-------------|-----------|
| LPG-532-BJB-ZA-S337 | Cross-line, green | | |

TECHNICAL SPECIFICATIONS

| | | |
|---|--|---------------|
| Marking: | II 2(1)G Ex db [op is Ga] IIC T4 Gb II 2(1)D Ex tb [op is Da] IIIC T135°C Db | |
| Certificate: | EU-Type Examination Certificate | |
| Operating temperature: | -10°C to +50°C | |
| Storage temperature range: | -20°C to +70°C | |
| Housing: | M18, Material: Ms 58 nickel plated | |
| Ingress protection: | IP67 | |
| Light Source: | Laser, green, 532nm, class 2 | |
| Maximum optical radiant power: | < 1 mW | |
| Pattern angle: | 25° | |
| Supply voltage, U _e : | 24 VDC ± 10% | |
| Absolute maximum supply voltage, U _m : | 30 VDC | |
| Maximum power dissipation: | 2.4 W | |
| Maximum current consumption: | 80 mA | |
| EMC, shock and vibration resistance: | Vibration: 30g over 20Hz to 2Khz. Shock: 100g for 3ms | |
| Laser lifetime: | 5000 h | |
| Connection cable: | TPU insulation, AWM 20236, 4+PE x 0.5mm ² , halogen free, shielded, leads numbering marked, oil resistant cable for trailing, length: 10m | |
| Accessories included: | <ul style="list-style-type: none"> • 2x nuts M18 • 1x Warning plate "LASER RADIATION. DO NOT STARE INTO BEAM. CLASS 2 LASER PRODUCT", self-adhesive for gluing near to the sensor. | |
| Safe equipotential bonding for Ex devices: | Ensure local equipotential bonding by means of a corrosion-resistant PE connection. The end of the cable must be connected outside the hazardous locations. | |
| Wiring and Connection: | Lead-No | Function |
| | 1 | 24 VDC ± 10% |
| | 2 | 0V |
| | 3 | DO-Output |
| | 4 | Disable Input |
| | yellow-green | PE/PA |
| white | Cable shield | |