

OL-LPA OBSTRUCTION LIGHTING FIXTURE

Zones 1, 2

Full catalogue available on our website: www.inpratex.com

ATEX VISUAL SIGNALLING DEVICES ZONES 1, 2 (gas)



The OL-LPA series of lighting fixtures are used to signal obstructions and are particularly suitable for use on towers or chimneys and high buildings.



EU-Type Examination Certificate

ITEM REFERENCES

Designation:	LED Lamp:	Item No.:
OL-LPA RED	E27- ±8W - 230 VAC	2A2601

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex d IIC T5 Gb
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Operating mode:	Continuous
Body and cover:	Low cooper content Aluminium Alloy
Globe:	Shock and temperature resistant borosilicate glass
Fresnel lens:	Shock and UV resistant Polycarbonate
Gasket:	Acid/Hidrocarbon resistant Silicone
Bolt and screws:	ST.ST.A2
Housing finish:	Epoxy coating. RAL 7000 (Grey)
Power supply:	230VAC
Frequency:	50/60 Hz
Lamp holder:	E27 - Direct connection to lamp holder
Cable entries:	2x 3/4" NPT (cable gland not included)

