

OSSP(T) STOPPING PLUGS, METAL (ON REQUEST)

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX INSTALLATION MATERIAL

ZONES 1, 2 (gas) & 21, 22 (dust)



Flameproof & Increased Safety stopping plugs, to block entries for maintenance of the flameproof and increased safety integrity of the equipment. Provides a means of blanking unused or spare entries.

Manufactured in brass and nickel plated brass.

Stainless steel 316L on request.



EU-Type Examination Certificate

For NPT threads in Ex d enclosures, no shoulder plugs must be used, in accordance with EN 60079-1.

ITEM REFERENCES (SUPPLIED ON REQUEST)

NPT:	Thread Length[ℓ]:	Hexagon/Round Dimensions D (mm):	Weight (g):	Item No.:
1/2"	15	27	30	7D0301
3/4"	16	32	55	7D0302
1"	18	40	100	7D0303
1-1/4"	19	50	160	7D0304
1-1/2"	21	55	265	7D0305
2"	24	70	430	7D0306
2-1/2"	27	82	650	7D0307
3"	30	98	920	7D0308
3-1/2"	32	112	1210	7D0309

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex db IIC Gb, Ex eb IIC Gb II 2D Ex tb IIIC Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-60°C to +110°C
Material:	Brass, nickel plated brass and stainless steel 316L (on request)
Gasket (washer):	Nylon
Ingress protection:	IP66/68

Marking Area

