ATEX INSTALLATION MATERIAL

Zones 1, 2, 21, 22

ZONES 1, 2 (gas) & 21, 22 (dust)

OSSP(T) STOPPING PLUGS, METAL (ON REQUEST)



Flameproof & Increased Safety stopping plugs, to block entries for maintenance of the flameproof and increased safety integrity of the equipment



Manufactured in brass and nickel plated brass. Stainless steel on request.

ITEM REFERENCES (SUPPLIED ON REQUEST)				
NPT:	Thread Length[ℓ]:	Round Dimensions (mm):	Weight (g):	Item No.:
1/2"	15	28	30	7D0301
3/4"	16	32	55	7D0302
1"	18	40	100	7D0303
1-1/4"	19	50	160	7D0304
1-1/2"	21	55	265	7D0305
2"	24	70	430	7D0306
2-1/2"	27	84	650	7D0307
3"	30	97	920	7D0308
3-1/2"	32	110	1210	7D0309

TECHNICAL SPECIFICATIONS			
Marking:	II 2G Ex d IIC / Ex eb IIC Gb II 2D Ex tb IIIC Db		
Certificate:	EU-Type Examination Certificate		
Operating conditions:	Indoor / Outdoor		
Material:	Brass, nickel plated brass and stainless steel (on request)		
Gasket (washer):	Nylon		
Ingress protection:	IP66/67		
Operating temperature:	-60°C to +110°C		



