

6-ELEMENT PENDANT STATIONS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

4



CONTROL & CONNECTION EQUIPMENT

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



The ATEX XAWP pendant control stations are suitable for all types of industry and primarily used on cranes.

Configuration:

1 white/black booted pushbutton, (with or without inter-lockable mechanism)
2 speeds, 2 NO contact per function, "Up" and "Down" twin arrows.

1 white/black booted pushbutton, (with or without inter-lockable mechanism)
2 speeds, 2 NO contact per function, "Left" and "Right" twin arrows.

1 Plug

1 emergency stop Ø40 mushroom turn to release, 1 NC contact, "Emergency Stop"



EU-Type Examination Certificate

ITEM REFERENCES

Designation:	Use:	Zones:	Item No.:
6-element pendant station with interlock	Indoor	1,2,22	3J1007
6-element pendant station without interlock	Indoor/Outdoor	1,2,21,22	3J1008

TECHNICAL SPECIFICATIONS

	With interlock:	Without interlock:
Marking:	II 2G Ex db eb IIC T6 Gb II 3D Ex tc IIIB T85°C Dc IP65	II 2G Ex db eb IIC T6 Gb II 2D Ex tb IIIC T85°C Db IP65
Certificate:	EU-Type Examination Certificate	
Operating temperature:	-20°C to +60°C	
Ingress protection:	IP65 according to EN/IEC 60529	
Material:	Glass fibre reinforced polyester (GRP)	
Dimensions:	590x98x76 mm	
Features of the contact block:	I _{th} = 10 A; U _i = 415 V	
	AC	U _e = 380 V; I _e = 1,9 A o U _e = 240 V; I _e = 3 A o U _e = 120 V; I _e = 6 A
	DC	U _e = 250 V; I _e = 0,27 A o U _e = 125 V; I _e = 0,55 A o U _e = 24 V; I _e = 2,87 A
Features of the LED pilot light:	Rated voltage: 24...254 V AC/DC Maximal current: 2...10 mA	
Mechanical endurance:	Head: 5 million operations - Contact block: 1 million operations	
Cable entries:	For cable Ø 10 to Ø 22 mm	