

8-ELEMENT PENDANT STATIONS V3

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



The ATEX XAWP pendant control stations are suitable for all types of industry and primarily used on cranes.

Configuration:

1 emergency stop Ø40 mushroom turn to release, 2NC+1NO "Emergency Stop"

1 red light 24-250V

1 selector switch 2 pos., 1NO

1 green light 24-250V

1 white/black bootable pushbutton with inter-lockable mechanism, 1 speeds, 1 NO contact per function, "up" and "down" arrows.

1 white/black bootable pushbutton with inter-lockable mechanism, 1 speeds, 1 NO contact per function, "left" and "right" arrows.



EU-Type Examination Certificate

4





CONTROL & CONNECTION EQUIPMENT

ITEM REFERENCES

Designation:	Use:	Zones:	Item No.:
8-element pendant station V3	Indoor/Outdoor	1,2,21,22	3J1011

TECHNICAL SPECIFICATIONS

Marking:	 II 2G Ex db eb mb IIC T6 Gb  II 2D Ex tb IIIC T85°C Db IP65
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +60°C
Ingress protection:	IP65 according to EN/IEC 60529
Material:	Glass fibre reinforced polyester (GRP)
Dimensions:	680x98x76 mm
Features of the contact block:	Ith = 10 A; Ui = 415 V
	AC Ue = 380 V; Ie = 1,9 A o Ue = 240 V; Ie = 3 A o Ue = 120 V; Ie = 6 A
	DC Ue = 250 V; Ie = 0,27 A o Ue = 125 V; Ie = 0,55 A o Ue = 24 V; Ie = 2,87 A
Features of the LED pilot light:	Rated voltage: 24...254 V AC/DC Maximal current: 2...10 mA
Mechanical endurance:	Head: 5 million operations - Contact block: 1 million operations
Cable entries:	For cable Ø 10 to Ø 22 mm