

PENDANT STATIONS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



The ATEX XAWP pendant control stations are suitable for all types of industry and primarily used on cranes.



The XAWP range is available with 2, 4, 6 or 8 pushbuttons with up to three contact blocks per operator. Custom double XAWP assemblies can be delivered to provide 12 or 16 way pendant control stations. The XAWP also features an optional double-step actuation mode for dual speed control.



ITEM REFERENCES

Designation:	Item No.:
2-element pendant station	XAWP029
4-element pendant station	XAWP049
6-element pendant station	XAWP069
8-element pendant station	XAWP089
12-element pendant station	XAWP069D
16-element pendant station	XAWP089D

TECHNICAL SPECIFICATIONS



Marking:	 II 2G Ex db eb IIC T6 Gb  II 2D Ex tb IIIC T85°C Db IP65
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +60°C
Ingress protection:	IP65 according to EN/IEC 60529
Material:	Glass fibre reinforced polyester (GRP)
Features of the contact block:	Ith = 10 A; Ui = 415 V
	AC Ue = 380 V; Ie = 1,9 A or Ue = 240 V; Ie = 3 A or Ue = 120 V; Ie = 6 A DC Ue = 250 V; Ie = 0,27 A or Ue = 125 V; Ie = 0,55 A or Ue = 24 V; Ie = 2,87 A
Features of the LED pilot light:	Rated voltage: 24...254 V AC/DC Maximal current: 2...10 mA
Mechanical endurance:	Head: 5 million operations - Contact block: 1 million operations
Cable entries:	For cable Ø 10 to Ø 22 mm

PENDANT STATIONS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

OPERATORS

Pushbuttons	White	XAWP9411
	Black	XAWP9412
	Green	XAWP9413
	Red	XAWP9414
	White	XAWP9411
Pilot lights	White	XLW5AV013-XAWP
 (24V ... 254V AC-DC)	Green	XLW5AV033-XAWP
	Red	XLW5AV043-XAWP
	Yellow	XLW5AV053-XAWP
	Blue	XLW5AV063-XAWP
	White	XLW5AV013-XAWP
Selector switch + contact	2 fixed positions - Black	XBW5AD21
	3 fixed positions - Black	XBW5AD33
Emergency Mushroom head (Ø 40)	Red	XBW5AS844-XAWP
Emergency Mushroom head (Ø 30)	Red	XBW5AS834-XAWP

ARROW FOR DOUBLE STEP PUSHBUTTON

ARROW FOR SINGLE STEP PUSHBUTTON

Type:	Item No.:	Type:	Item No.:
UP	ZBWY4953	UP	ZBWY4951
DOWN	ZBWY2956	DOWN	ZBWY2954
RIGHT	ZBWY4903	RIGHT	ZBWY4901
LEFT	ZBWY2906	LEFT	ZBWY2904
FORWARD	ZBWY4965	FORWARD	ZBWY4963
REVERSE	ZBWY2968	REVERSE	ZBWY2966
		FAST UP	ZBWY4952
		FAST DOWN	ZBWY2955
		FAST RIGHT	ZBWY4902
		FAST LEFT	ZBWY2905
		FAST FORWARD	ZBWY4964
		FAST REVERSE	ZBWY2967
		I	ZBWY4980
		O	ZBWY2931
		O - I	ZBWY2178
		I - II	ZBWY2179
		I - O - II	ZBWY2186
		EMERGENCY STOP	ZBWY2330

