

EX E PLASTIC CABLE GLAND - NON-ARMoured CABLE

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CABLE GLANDS

ZONES 1, 2 (gas) & 21, 22 (dust)



Ex e plastic cable glands (black) and Ex i plastic cable glands (blue), valid for potentially explosive atmospheres.

For hazardous areas on oil platforms, in dangerous goods warehouses or in chemical industries we offer EX cable glands with various types of protection complying with ATEX or IECEx.



EU-Type Examination Certificate

ITEM REFERENCES

	Metric:	Type:	Cable diameter:		Length L:	Length TL:	Width SW:	Item No.:
			Min:	Max:				
	M12x1,5	HIBM	3	6,5	10	29-34	15	7A0201
	M16x1,5	HIBM	4	10	10	31-37	19	7A0202
	M20x1,5	ESKE/1	7	13	10	36-45	24	7A0102
	M25x1,5	ESKE/1	10	17	10	38-47	29	7A0103
	M32x1,5	ESKE/1	13	21	12	42-51	36	7A0104
	M40x1,5	ESKE/1	17	28	12	52-65	46	7A0105
	M50x1,5	ESKE/1	23	35	14	59-72	55	7A0106
	M63x1,5	ESKE/1	34	48	15	64-78	68	7A0107
	M12x1,5	HIBM	3	6,5	10	29-34	15	7A0301
	M16x1,5	HIBM	4	10	10	31-37	19	7A0302
	M20x1,5	ESKE/1	7	13	10	36-45	24	7A0109
	M25x1,5	ESKE/1	10	17	10	38-47	29	7A0110
	M32x1,5	ESKE/1	13	21	12	42-51	36	7A0111
	M40x1,5	ESKE/1	17	28	12	52-65	46	7A0112
	M50x1,5	ESKE/1	23	35	14	59-72	55	7A0113
	M63x1,5	ESKE/1	34	48	15	64-78	68	7A0114

TECHNICAL SPECIFICATIONS TYPE HIBM

Marking:	II 2G Ex e IIC Gb II 2D Ex tb IIIC Db IP66/68
Certificate:	EU-Type Examination Certificate
Operating conditions:	Indoor / Outdoor
Material:	Polyamide
Protection class:	IP66 / IP68
Operating temperature:	-40°C to +70°C

TECHNICAL SPECIFICATIONS TYPE ESKE/1

Marking:	II 2G Ex eb IIC Gb II 2D Ex tb IIIC Db
Certificate:	EU-Type Examination Certificate
Operating conditions:	Indoor / Outdoor
Material:	Gland Polyamide, Gasket EPDM
Protection class:	IP66 / IP68 (5 bar 30 min)
Operating temperature:	-40°C to +75°C