

SL 150 COMBINED STATUS LIGHTS - GRP

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX VISUAL SIGNALLING DEVICES ZONES 1, 2 (gas) & 21, 22 (dust)



SL 150 combined status lights in GRP. This set of signalisation is certified for ATEX areas 1-2 for gas and 21 to 22 for dust.

It is dedicated Oil & Gas, chemical, petrochemical, pharmacy industries, marine and offshore applications. It is design for corrosive environments and hazardous areas.

Possibility to pilot all, or separately the beacons via a telephone line.



EU-Type Examination Certificate

ITEM REFERENCES

Model:	Power consumption:	Weight:	Article No.:
SL-150-A20 24V - 2 beacons	12 - 48V DC	8,9 kg	2A1901
SL-150-A20 220V - 2 beacons	100 - 240V AC	8,9 kg	2A1902
SL-150-B3J 24V - 2 beacons + junction box	12 - 48V DC	13,1 kg	2A1903
SL-150-B3J 220V - 2 beacons + junction box	100 - 240V AC	13,1 kg	2A1904
SL-150-B30 24V - 3 beacons	12 - 48V DC	13,1 kg	2A1905
SL-150-B30 220V - 3 beacons	100 - 240V AC	13,1 kg	2A1906
SL-150-C4J 24V - 3 beacons + junction box	12 - 48V DC	17,4 kg	2A1907
SL-150-C4J 220V - 3 beacons + junction box	100 - 240V AC	17,4 kg	2A1908
SL-150-C40 24V - 4 beacons	12 - 48V DC	17,4 kg	2A1909
SL-150-C40 220V - 4 beacons	100 - 240V AC	17,4 kg	2A1910
SL-150-D5J 24V - 4 beacons + junction box	12 - 48V DC	21,6 kg	2A1911
SL-150-D5J 220V - 4 beacons + junction box	100 - 240V AC	21,6 kg	2A1912

Lens colour: Red, Amber, Blue, Green, Clear

TECHNICAL DATA

Marking:	II 2G Ex d IIC T4...T6 Gb II 2D Ex tb IIIC T135°C...T85°C
Certificate:	EU-Type Examination Certificate
Operating mode:	Steady, rotary, fixed or blinking
Housing:	ENCLOSURE: Glass Reinforced Polyester. LENS: Tempered borosilicate glass 3.3. FRAME: Stainless Steel 316L
Housing colour:	Black (RAL 9004) Red (RAL 3001) Yellow (RAL 1018) Blue (RAL 5005)
Power:	LED 10W
Light intensity:	312 Cd
Operating temperature:	-40°C to +70°C
Ingress protection:	IP66/67
Cable entries:	3xM20x1,5 holes

