

SINGLE PUSHBUTTON

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)






Ex e Pushbutton made of glass fibre reinforced polyester for application in hazardous areas.
Tags: white (bw), black (bb), red (br), green (bg) or yellow (by).

Can be supplied with M20 cable glands for armored or non-armored cable.





EU-Type Examination Certificate





ITEM REFERENCES

Designation:		Item No.:
	Pushbutton 1NO+1NC - M20 Plastic cable gland	3J0601
	Pushbutton 2NC - M20 Plastic cable gland	3J0602
	Pushbutton 2NO - M20 Plastic cable gland	3J0603
	Pushbutton 1NO+1NC - M20 Brass Cable Gland	3J0604
	Pushbutton 2NC - M20 Brass Cable Gland	3J0605
	Pushbutton 2NO - M20 Brass Cable Gland	3J0606
	Pushbutton 1NO+1NC - M20 Nickel-Plated Brass Cable Gland	3J0607
	Pushbutton 2NC - M20 Nickel-Plated Brass Cable Gland	3J0608
	Pushbutton 2NO - M20 Nickel-Plated Brass Cable Gland	3J0609

TECHNICAL SPECIFICATIONS

Marking:	 II 2G Ex ed IIC T6 Gb  II 2D Ex tb IIIC T80°C
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Cable entries:	1xM20x1,5

INTERNAL CONTACT MODULE

	
Marking:	 II 2G Ex de IIC Gb  I M2 Ex de I Mb
Certificate:	EU-Type Examination Certificate
Operating temperature:	-55°C to +60°C
Ingress protection:	IP20
Nominal isolation voltage:	690 V
Voltage range:	
400 V	400 V 110 V 24 V
Utilization categories:	
AC-12	AC-15 DC-13 DC-13
Current range:	
16 A	10 A 0,5 A 1 A