

EX TELEPHONE FERNTel 3 (ANALOGUE)

Zones 2, 22

Full catalogue available on our website: www.inpratex.com

ATEX COMMUNICATIONS

ZONES 2 (gas) & 22 (dust)



Analogue desk/wall telephone for applications in potentially explosive areas (zones 2 and 22). This telephone comprises a housing made of impact-resistant thermoplastic and is certified according to ATEX. In the field of the chemical and petrochemical industry potentially explosive atmospheres occur during production procedures caused by e.g. gases, vapours or mist.

The impact-resistant thermoplastic housing as well as the use of stainless steel screws add further special advantages to the FernTel 3.

Moreover, the telephone may effortlessly be converted from a wall-mounted device to a desk telephone and vice versa.



EU-Type Examination Certificate

ITEM REFERENCES

Designation:	Model:	Item No.:
FernTel 3	Without display, with spiral cord	4A0201
FernTel 3	With display, with spiral cord	4A0202
FernTel 3	Without display, with armoured cord	4A0203
FernTel 3	With display, with armoured cord	4A0204

TECHNICAL SPECIFICATIONS

Marking:	II 3G Ex nA ic IIC T5 Gc II 3D Ex tc ic IIIC T80°C Dc
Certificate:	EU-Type Examination Certificate
Ringing frequency:	Settable: 16 Hz to 68 Hz
Supply voltage:	24 V...66 V DC
Housing:	Impact-resistant thermoplastic
Weight:	Approx. 2,3 kg
Operating temperature:	-20°C to +55°C
Ingress protection:	IP65
Cable entries:	1xM20x1,5 plastic cable gland / 1xM20x1,5 plastic plug

