
ZONES 0, 1, 2 (gas) & Mines









The tail-cap switch provides momentary or constant-on functionality. Power comes from 2 AAA premium batteries (included).

Submersible up to 1 meter.







- Momentary or constant-on flashlight
- Engineered polymer housing
- Waterproof
- Built-in pocket/belt clip

- Sharp focused beam for distance illumination
- Single tail switch
- Impact & chemical resistant
- High-efficiency deep parabolic reflector

ITEM REFERENCES	
Model:	Item No.:
XPP-5410G	1E0702

TECHNICAL SPECIFICATIONS	
Marking: ATEX	I M1 Ex ia op is Ma II 1G Ex ia op is IIC T3 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga
Certificate:	EU-Type Examination Certificate
Ingress protection:	IP67
LED:	CREE LED (+50,000+ hours LED life)
Run time:	18 h
Luminous flux:	30 lm
Beam distance:	40 m
Batteries:	2 x AAA (included)
Weight:	53,9 g
Dimensions:	2,3 cm (head diameter) 1,80 cm (handle diameter) 14,7 cm (length)
Operating temperature:	-20°C to +40°C