

XPP-5414GX DUAL-LIGHT FLASHLIGHT WITH MAGNET

Zones 0, 1, 2

Full catalogue available on our website: www.inpratex.com

ATEX FLASHLIGHTS

ZONES 0, 1, 2 (gas)



This Intrinsically Safe (cETLus, ATEX Zone 0 and IECEx) Dual-Light™ LED flashlight offers peak performance in hazardous work environments. Use the top-mounted buttons to trigger the flashlights focused distance lighting and the floodlights expansive close-up illumination.

Maximize the safety and functionality benefits by simultaneously activating both lights in Dual-Light™ Mode. Features easy-to-use top-mounted switches, durable glass-filled nylon polymer housing, an integrated magnet on base, and a reversible pocket clip.

Submersible up to 1 meter.



ITEM REFERENCES

Model:	Item No.:
XPP-5414GX	1E2301

TECHNICAL SPECIFICATIONS

Marking: ATEX	II 1G Ex ia op is IIC T3 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135°C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga
Certificate:	EU-Type Examination Certificate
Case material:	Engineered polymer
Ingress protection:	IP67
Candela:	3100cd
Run time:	Flashlight: 24 h Floodlight: 24 h Dual Light: 24 h
Luminous flux:	Flashlight: 120 lm Floodlight: 120 lm Dual Light: 120 lm
Beam distance:	111 m approx.
Power source:	2 x AA (not included)
Weight:	116 g
Dimensions:	33 mm (head diameter) 22 mm (handle diameter) 159 mm (length)
Operating temperature:	-20°C to +40°C