

# XPP-5418GX FLASHLIGHT

Zones 0, 1, 2

Full catalogue available on our website: [www.inpratex.com](http://www.inpratex.com)

## ATEX FLASHLIGHTS

## ZONES 0, 1, 2 (gas)

This flashlight is cETLus, ATEX Zone 0, IECEx, and INMETRO certified Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dust may be present.

This light uses an LED rated at 200 lumens that work in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 143 meters. The tail switch provides momentary or constant-on functionality.

Submersible up to 1 meter.

- Momentary or constant-on flashlight
- Sharp focused flashlight beam for distance illumination
- Polymer housing
- Non-slip grip
- Dustproof/Waterproof
- Impact & chemical resistant
- Tail switch
- LED technology



### ITEM REFERENCES

Model:	Item No.:
XPP-5418GX	1E2401

### TECHNICAL SPECIFICATIONS

Marking: ATEX	II 1G Ex ia op IIC T3 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga
Certificate:	EU-Type Examination Certificate
Case material:	Engineered polymer
Ingress protection:	IP67
Candela:	5129cd
Run time:	10,5 h
Luminous flux:	200 lm
Beam distance:	143 m
Power source:	3 x AA (not included)
Weight:	153 g
Dimensions:	38mm (head diameter)   19mm x 35mm (handle diameter)   142mm (length)
Operating temperature:	-20°C to +40°C