

XPP-5454G DUAL LIGHT HEADLAMP

Zones 0, 1, 2

Full catalogue available on our website: www.inpratex.com

ATEX HEADLAMPS

ZONES 0, 1, 2 (gas)

This 3 AAA multi-function Dual-Light headlamp is cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe.



This headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat.

The dual top mounted switches provide user-selectable high or low-brightness spotlight, high or low-brightness floodlight operation and our exclusive Dual-Light design...the ability to turn on both the spotlight and the floodlight at the same time for maximum user safety and lighting versatility.



Heavy-duty rubber strap for hard hat applications.

Power comes from 3 AAA batteries (included).



EU-Type Examination Certificate

ITEM REFERENCES

Model:	Item No.:
XPP-5454G	1E0801

TECHNICAL SPECIFICATIONS

Marking: ATEX	II 1G Ex ia IIC T3 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T3 CLASS II & III GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga
Certificate:	EU-Type Examination Certificate
Ingress protection:	IP67
Light Source:	CREE LED (50,000 + hours LED life)
Run time:	Flashlight: High 5 h Low 16,25 h Floodlight: High 5,25 h Low 16,75 h Dual-Light: 3,5 h
Luminous flux:	Flashlight: High: 115 lm Low: 60 lm Floodlight: High: 120 lm Low: 60 lm Dual-Light: 160 lm
Beam distance:	82 m / 60 m
Batteries:	3 x AAA (included)
Weight:	94 g
Dimensions:	66 x 45 x 53 mm
Operating temperature:	-20°C to +40°C