

# XPP-5462GX LOW-PROFILE DUAL-LIGHT HEADLAMP

Zones 0, 1, 2

Full catalogue available on our website: [www.inpratex.com](http://www.inpratex.com)

2



FLASHLIGHTS & HEADLAMPS

## ATEX HEADLAMPS

ZONES 0, 1, 2 (gaz)

Intrinsically Safe Low-Profile Dual-Light™ Headlamp is cULus, ATEX and IECEx listed Intrinsically Safe and is designed specifically to work on fire helmets and hard-hats that have a flip-up face shield.



Spot High Spot Low Flood High Flood Low Dual



EU-Type Examination Certificate



Focused high/low-brightness spotlight beam for distance illumination.  
 Unfocused high/low-brightness wide-beam floodlight for close-up illumination.  
 Dual-Light (spotlight and floodlight on at the same time) for maximum versatility.

Submersible up to 1 meter.

The XPP-5462GX includes a heavy-duty rubber head strap for use on a fire helmet or hard-hat.

### ITEM REFERENCES

Model:	Item No.:
XPP-5462GX	1E1801

### TECHNICAL SPECIFICATIONS

Marking: ATEX	II 1G Ex ia IIC T4 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G CLASS I ZONE 0 GRP IIC T4 CLASS II ZONE 20 IIIC T135°C
Certificate:	EU-Type Examination Certificate
Ingress protection:	IP67
Lamp:	LED
Run time:	Flashlight: High 6,75 h   Low 25 h Floodlight: High 7 h   Low 25 h Dual-Light: 6 h
Luminous flux:	Flashlight: High 275 lm   Low: 100 lm Floodlight: High: 250 lm   Low: 100 lm Dual-Light: 310 lm
Beam distance:	106 m
Batteries:	3 x AA batteries (included)
Weight:	265 g
Dimensions:	32 x 95 x 25 mm
Operating temperature:	-20°C a +40°C