

XPP-5564RX DUAL LIGHT ANGLE LIGHT 4AA

Zones 0, 1, 2, 20, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX FLASHLIGHTS

ZONES 0, 1, 2 (gas) & 20, 21, 22 (dust)

The XPP-5564RX Intrinsically Safe Angle Light is equipped as a flashlight, floodlight, and Dual-Light engineered for the brutal, challenging nature of fire and rescue. ATEX ZONE 0/20, cETLus, and IECEx certified Intrinsically Safe, the XPP-5564RX is geared for the fight in hazardous scenarios.

In spotlight mode, this angle lamp offers user-selectable brightness settings of 250 and 110 lumens with a 469-meter beam distance. With a bolstered 54,900 candela at your arsenal, the spotlight's tight beam pierces through smoke and haze with ultra-clarity at long distances. The floodlight mode has user-selectable brightness settings of 270 and 120 lumens. A battery status indicator glows green at full battery and shows red when battery is low.



EU-Type Examination Certificate



Dual-Light mode on the XPP-5564RX combines the long-range visibility of the flashlight with the wide-area illumination of the floodlight, enabling users to discern objects in the distance while maintaining orientation. The floodlight's 45° downward tilt is meticulously designed to mitigate the risk of slips and falls, ensuring that both light sources work in tandem to navigate through treacherous environments safely.



ITEM REFERENCES

Model:	Item No.:
XPP-5564RX	1E2601

TECHNICAL SPECIFICATIONS

Marking: ATEX	 II 1G Ex ia IIC T4 Ga  II 1D Ex ia IIC T135C Da
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV1 GRPS E-G T135°C CLASS I ZONE 0 AEx ia IIC T3 Ga
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Case material:	PC/ABS. Body Color: Red/Black
Ingress protection:	IP67
Drop rating:	2 m
Run time:	High: 6 h Low: 18 h Floodlight: High 8,5 h Low 28 h High Dual-Light: 5,5 h
Luminous flux:	High: 250 lm Low: 110 lm Floodlight: High 270 lm Low 120 lm High Dual-Light: 280 lm
Beam distance:	469 m (High) 171 m (Low)
Candela:	High: 54900 cd Low: 7333 cd
Weight:	3122 g
Dimensions:	159 x 70 x 64 mm Head diameter: 70 mm
Power source:	4AA batteries (included)