

XPR-5522GMX RECHARGEABLE DUAL-LIGHT FLASHLIGHT W/ MAGNETS

Zones 0, 1, 2

Full catalogue available on our website: www.inpratex.com

ATEX FLASHLIGHTS

ZONES 0, 1, 2 (gas)

The XPR-5522GMX Rechargeable Dual-Light Flashlight w/Dual Magnets is cETLus, ATEX, IECEx, and MSHA listed Intrinsically Safe Permissible for use in both above and below ground hazardous locations where explosive gases and dusts may be present.

It uses an LED rated at 240 lumens that work in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 178 meters. A 175 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination.

Powered by an integrated Lithium-ion rechargeable battery.

Wall or Vehicle Mounted Charger included.



EU-Type Examination Certificate



Flashlight



Floodlight



Dual-Light



Dual Magnets



ITEM REFERENCES

Model:	Item No.:
XPR-5522GMX	1E1702

TECHNICAL SPECIFICATIONS

Marking: ATEX	II 1G Ex ia op is IIC T3 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T3 CLASS II DIV 1 GRPS E-G T3 & Class III T165°C CLASS I ZONE 0 AEx ia IIC T3 Ga ZONE 20 GROUP IIIC T165°C
Certificate:	EU-Type Examination Certificate
Ingress protection:	IP54
LED:	240 lm
Run time:	Flashlight: 8 h Floodlight: 8,5 h Dual Light: 4,75 h
Luminous flux:	Flashlight: 240 lm Floodlight: 175 lm Dual-Light: 400 lm
Beam distance:	178 m
Rechargeable battery:	Lithium-ion
Weight:	280 g
Dimensions:	53 mm (head diameter) 33x43 mm (diameter) 188 mm (length)
Operating temperature:	-10°C to +40°C

