

# XPR-5562GX USB LOW-PROFILE DUAL-LIGHT HEADLAMP

Zones 0, 1, 2

Full catalogue available on our website: [www.inpratex.com](http://www.inpratex.com)

## ATEX HEADLAMPS

ZONES 0, 1, 2 (gaz)

The USB Intrinsically Safe Rechargeable Dual-Light Headlamp is cULus, ATEX and IECEx listed Intrinsically Safe and is designed to work on hard-hats and fire helmets that have a flip-up face shield.

The unique low-profile shape allows you to work without removing the headlamp when raising or lowering a face shield. The XPR-5562GX is manufactured from engineered polymer and features a multi-position tilt head design. Both the spotlight and the floodlight use LED technology with advanced (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern.

Enlarged front-mounted dual switches provide easy access to the spotlight for distance illumination, the floodlight for close-up illumination, and Dual-Light for maximum lighting, versatility, and user safety.

The XPR-5562GX includes a heavy-duty rubber head strap, a 4 foot USB magnetic coupler charge card, and is powered by a Li-Ion rechargeable battery.



EU-Type Examination Certificate



### ITEM REFERENCES

Model:	Item No.:
XPR-5562GX	1E2001

### TECHNICAL SPECIFICATIONS

Marking: ATEX	II 1G Ex ia op is IIC T4 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G T135°C CLASS I ZONE 0 AEx ia op is IIC T4 Ga
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Case material:	Engineered polymer
Spotlight Lumens/Runtime:	HIGH: 275 lm, 6 hrs. runtime   LOW: 100 lm, 15 hrs. runtime
Floodlight Lumens/Runtime:	HIGH: 250 lm, 6 hrs. runtime   LOW: 100 lm, 15 hrs. runtime
Dual-light Lumens/Runtime:	300 lm, 5 hrs. runtime
Candela:	HIGH: 3,660
Beam distance:	120 m
Ingress protection:	IP67
Drop rating:	2 meters
Dimensions:	LENGTH: 31 mm   WIDTH: 95 mm   DEPTH: 25 mm
Weight:	164 g
Battery:	Integrated Li-ion

