

XPR-5568RX RECHARGEABLE DUAL-LIGHT ANGLE LIGHT

Zones 0, 1, 2

Full catalogue available on our website: www.inpratex.com

ATEX FLASHLIGHTS

ZONES 0, 1, 2 (gas) & Mines



The XPR-5568RX Intrinsically Safe angle light is a flashlight, a floodlight and a Dual-Light angle light that is cULus, ATEX, IECEx and MSHA certified Intrinsically Safe. The flashlight rotates 90 degrees up and down with a 45 degree downward angled floodlight.

The flashlight setting offers user-selectable brightness settings of 200, 110 and 60 Lumens with a 401 meter beam distance. The ultra-tight beam is perfect for cutting through smoke and lighting up objects at great distances. The floodlight setting has user-selectable brightness settings of 100, 40 and a "Survival Mode" of 20 lumens that provides just enough light in an emergency situation with a run-time of 27 hours.

Battery charge status indicator (only with rechargeable battery)
Rechargeable Lithium-ion Battery Pack included.
Wall or Vehicle Mounted Charger.



EU-Type Examination Certificate



ITEM REFERENCES

Model:	Item No.:
XPR-5568RX	1E1302

TECHNICAL SPECIFICATIONS

Marking: ATEX	I M1 Ex ia op is I Ma II 1G Ex ia op is IIC T3 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV1 GRPS E-G T135°C CLASS I ZONE 0 AEx ia IIC T3 Ga
Certificate:	EU-Type Examination Certificate
Ingress protection:	IP67
LED:	CREE LED (50,000+ hours LED life)
Run time:	Flashlight: High 7 h Medium 15 h Low 27 h Floodlight: High 7 h Medium 15 h Low 27 h Dual-Light: 7 h
Luminous flux:	Flashlight: 200 lm (High) 110 lm (Medium) 60 lm (Low) Floodlight: 100 lm (High) 40 lm (Medium) 20 lm (Low) Dual-Light: 205 lm
Beam distance:	401 m (High) 250 m (Medium) 187 m (Low)
Weight:	301 g (with battery)
Dimensions:	53 mm (bezel diameter) 66 mm (width) 168 mm (length) 66 mm (depth)
Rechargeable battery:	Lithium-ion
Recharge time:	4 h
Operating temperature:	-20°C to +40°C