

# XPR-5572RA RECHARGEABLE ANGLE FLASHLIGHT

Zones 1, 2

Full catalogue available on our website: [www.inpratex.com](http://www.inpratex.com)

EX LIGHTING

## ATEX FLASHLIGHTS

ZONES 1, 2 (gas)



The XPR-5572RA rechargeable Intrinsically Safe multi-function Dual-Light angle light is a flashlight, a floodlight and a Dual-Light angle light that is ATEX and IECEx certified Intrinsically Safe.

The flashlight setting offers 3 user-selectable brightness settings of 200, 100 and 60 Lumens plus a strobe feature with a 267 meter beam distance. The ultra-tight beam is perfect for cutting through smoke. The floodlight setting has 3 user-selectable brightness settings of 200, 100 and a "Survival Mode" of 20 lumens that provides just enough light in an emergency situation with a run-time of 3 ½ days.

Battery charge status indicator (only with rechargeable battery)



EU-Type Examination Certificate

Rechargeable Lithium-ion battery pack included.  
Wall or vehicle mounted charger.



### ITEM REFERENCES

Model:	Article No.:
XPR-5572RA	1E1102

### TECHNICAL DATA

Marking: ATEX	Ex II 2G Ex ia IIC T4 Gb
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G CLASS I ZONE 1 AEx ia IIC T4 Gb CLASS II ZONE 20 IIIC
Certificate:	EU-Type Examination Certificate
Ingress protection:	IP67
LED:	CREE LED (50,000+ hours LED life)
Run-time:	Flashlight: High 6 h   Medium 11,5 h   Low 22,5 h Floodlight: High 6h   Medium 11,5 h   Survival 30 h Dual-Light: 6 h
Luminous flux:	Flashlight: 200 lm (high)   100 lm (medium)   60 lm (low) Floodlight: 200 lm (high)   100 lm (medium)   20 lm (Survival) Dual-Light: 200 lm
Beam distance:	267 m
Rechargeable battery:	Lithium-ion
Recharge time:	6 h
Weight:	388 g
Dimensions:	70 mm (bezel diameter)   80 mm (width)   192 mm (length)   77 mm (depth)
Operating temperature:	-20°C to +40°C