

XPR-5580R RECHARGEABLE DUAL-LIGHT LANTERN

Zones 0, 1, 2

Full catalogue available on our website: www.inpratex.com

ATEX FLASHLIGHTS

ZONES 0, 1, 2 (gas)



EU-Type Examination Certificate



The XPR-5580R Intrinsically Safe Dual-Light lantern is a flashlight, a floodlight and a Dual-Light that is cULus, ATEX, and IECEx certified intrinsically safe.

The flashlight setting offers 3 user-selectable brightness settings of 210, 100 and 30 lumens with a 635 meter beam distance. The flashlight beam is perfect for cutting through smoke and lighting up objects at great distances. The floodlight setting has 3 user-selectable brightness settings of 200, 100 and a "Survival Mode" of 30 lumens that provides just enough light in an emergency situation with a run-time of 65 hrs.



Rechargeable Lithium-ion battery pack included.
Wall or vehicle mounted charger.

ITEM REFERENCES

Model:	Referencia:
XPR-5580R	1E1202

TECHNICAL SPECIFICATIONS

Marking: ATEX	II 1G Ex ia IIC T4 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G CLASS I ZONE 0 GRP IIC T4 CLASS II ZONE 20 IIIC T135°
Certificate:	EU-Type Examination Certificate
Ingress protection:	IP67
LED:	CREE LED (50,000+ hours LED life)
Run time:	Flashlight: High 12 h Medium 19 h Survival 65 h Floodlight: High 14 h Medium 19 h Survival 65 h Dual-Light: 9 h 15
Luminous flux:	Flashlight: 210 lm (High) 100 lm (Medium) 30 lm (Survival) Floodlight: 210 lm (High) 100 lm (Medium) 30 lm (Survival) Dual-Light: 300 lm
Beam distance:	635 m / 257 m / 164 m
Rechargeable battery:	Lithium-ion
Recharge time:	6 h
Weight:	935 g
Dimensions:	12 cm (head diameter) 12 cm (width) 14 cm (depth) 20 cm (length)
Operating temperature:	-20°C to +40°C